

A	1	2	3	4	5	6	7																																																																								
B																																																																															
C																																																																															
D																																																																															
E	<p style="text-align: center;">SPECIFICATIONS</p> <table border="1"> <tr> <td>HOUSING</td> <td>POLY CARBONATE(PC) UL94V2</td> </tr> <tr> <td>CONTACT BLADE</td> <td>HIGH STRENGTH COPPER ALLOY</td> </tr> <tr> <td>MATERIAL</td> <td>100 MICRON NICKEL UNDERPLATED</td> </tr> <tr> <td>PLATING TYPE</td> <td>8% PHOSPHOR BRONZE</td> </tr> <tr> <td>PLATING THICKNESS:</td> <td>GOLD PLATED 6U"</td> </tr> <tr> <td>OPERATING TEMP</td> <td>-40°C TO 125°C</td> </tr> <tr> <td>CURRENT RATING</td> <td>250V AC MAX AT 2A</td> </tr> <tr> <td>DIELECTRIC</td> <td>500V AC</td> </tr> <tr> <td>INSULATION RES</td> <td>500MEGAOHMS</td> </tr> </table> <p style="text-align: center;">COMPLIES WITH FCC68/F</p>							HOUSING	POLY CARBONATE(PC) UL94V2	CONTACT BLADE	HIGH STRENGTH COPPER ALLOY	MATERIAL	100 MICRON NICKEL UNDERPLATED	PLATING TYPE	8% PHOSPHOR BRONZE	PLATING THICKNESS:	GOLD PLATED 6U"	OPERATING TEMP	-40°C TO 125°C	CURRENT RATING	250V AC MAX AT 2A	DIELECTRIC	500V AC	INSULATION RES	500MEGAOHMS																																																						
HOUSING	POLY CARBONATE(PC) UL94V2																																																																														
CONTACT BLADE	HIGH STRENGTH COPPER ALLOY																																																																														
MATERIAL	100 MICRON NICKEL UNDERPLATED																																																																														
PLATING TYPE	8% PHOSPHOR BRONZE																																																																														
PLATING THICKNESS:	GOLD PLATED 6U"																																																																														
OPERATING TEMP	-40°C TO 125°C																																																																														
CURRENT RATING	250V AC MAX AT 2A																																																																														
DIELECTRIC	500V AC																																																																														
INSULATION RES	500MEGAOHMS																																																																														
F																																																																															
G	<p style="text-align: center;">ROHS compliant</p> <p style="text-align: center;">Unit: mm</p>																																																																														
H	<table border="1"> <tr> <td>Scale</td> <td>Free</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>TOLERANCE</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>X.X</td> <td>±0.2</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>X.XX</td> <td>±0.10</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>X.XXX</td> <td>±0.05</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>DIM</td> <td>TOL</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>X.°</td> <td>±3°</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>X.X°</td> <td>±1.0°</td> <td>⊙</td> <td>Drawn</td> <td>13.06.2016</td> <td>Joanna</td> <td></td> <td></td> </tr> <tr> <td>Angle</td> <td>TOL</td> <td>Id.</td> <td>Modification</td> <td>Date</td> <td>Name</td> <td></td> <td></td> </tr> </table>							Scale	Free							TOLERANCE								X.X	±0.2							X.XX	±0.10							X.XXX	±0.05							DIM	TOL							X.°	±3°							X.X°	±1.0°	⊙	Drawn	13.06.2016	Joanna			Angle	TOL	Id.	Modification	Date	Name		
Scale	Free																																																																														
TOLERANCE																																																																															
X.X	±0.2																																																																														
X.XX	±0.10																																																																														
X.XXX	±0.05																																																																														
DIM	TOL																																																																														
X.°	±3°																																																																														
X.X°	±1.0°	⊙	Drawn	13.06.2016	Joanna																																																																										
Angle	TOL	Id.	Modification	Date	Name																																																																										
1	2	3	4	5	6	7	H																																																																								
<table border="1"> <tr> <td rowspan="2" style="text-align: center;">ASSMANN WSW components</td> <td>Customer-r-No.</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>ASSMANN WSW-No.</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>Drawing-No.</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>ASS 7277 CO</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>Replace</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>rev00</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>Sheet</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </table>							ASSMANN WSW components	Customer-r-No.						ASSMANN WSW-No.							Drawing-No.							ASS 7277 CO							Replace							rev00							Sheet																														
ASSMANN WSW components	Customer-r-No.																																																																														
	ASSMANN WSW-No.																																																																														
	Drawing-No.																																																																														
	ASS 7277 CO																																																																														
	Replace																																																																														
	rev00																																																																														
	Sheet																																																																														