



NOTES:

1. RESISTOR: 10K OHMS  
±20%. 1/4 WATT.
2. RESISTOR ASSEMBLY TO MEET FORD  
ENG. SPEC. ES-F57B-14A601-A

CUSTOMER: FORD  
CUSTOMER PART#: F57B-14A601-A

METRIC

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN BRACKETS [ ] ARE INCHES
UNLESS OTHERWISE SPECIFIED, DIMENSIONS DO NOT INCLUDE PLATING.
⊙ DENOTES CRITICAL CHARACTERISTICS.
CPK DENOTES CPK DIMENSIONS, -MINIMUM CPK VALUE
⊠ DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS
CP DENOTES CP DIMENSIONS, -MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS SHOWN ON DRAWING AND INITIALLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE

NO	COMPONENT NO	DESCRIPTION	QTY/M	U/M
BILL OF MATERIAL				

LTR	DATE	REVISION	CHK	APD
D	10/16/97	38698C-REVISED & REDRAWN IN NEW STRUCTURE GNK		
E	04/24/02	82123D-CHG. TOLERANCES PJM		
F	05/15/07	85439D-REDRAWN IN UG GMB		

COPIES TO	MATL SPEC
1 9 18	FINISH
2 10 19	DRW G. KERN
3 12 20	DATE 10/08/97
4 13 21	SCALE 4:1
5 14 23	CHK SUPER DR
6 15 33	DATE
7 16 43	APPD
8 17 53	DATE
TOLERANCE UNLESS OTHERWISE SPECIFIED	
ONE PLACE DEC +/- .3	
THREE PLACE DEC +/- .100	
ANGULAR +/- .1°	
3RD ANGLE PROJECTION	
TITLE RESISTOR ASSEMBLY	
REVISION DRWG. NO. 02400105Z	
OUTLINE	

